

True Flat All-in-One Touch POS System

- Industrial-Grade Motherboard.
- Led back light technology for brightness and Clarity.
- Resistive or capacitive touch panel optional.
- True flat design enhances the friendly interface between human beings and machine.
- ABS shell brings a perfect combination of stunning appearance and high intensity.



JAW-RH318











Artistic streamline design

Flattened bottom makes it stable on a table

Porous in the back propitious to emit heat, uninterrupted and long time use

Prepositive USB interfaces make the connection of peripherals easily

Specifications

Item		Specifications
CPU	Intel 1037U	Intel® Celeron® 1037U, Dual Core, 2M Cache, 1.8Ghz
	Intel J1900	Intel® Celeron® J1900, Quad Core, 2M Cache, 2.0Ghz
	Intel i3	Intel® Core® i3-3217U, Dual Core, 3M Cache, 1.8Ghz
OS	Supporting System	Windows xp, Windows 7, Windows 10, POSReady 2009 / POSReady 7
Appearance	Color	White / Black / Red
Main	Memory	DDR3 2GB (up to 8GB)
	Storage	2.5" SATA 500G HDD & 32G / 64G SSD
Primary Display	LCD	15-inch new original Sharp LED backlight LCD
	Resolution	1024 * 768
	Customer Display	8-Bit LED customer display
	Touch Panel	15-inch 5-wire high temperature resistive touch panel from Taiwan Abon
Interfaces	VGA	1 * VGA
	USB	6 * USB(Rear 4 * USB; Side 2 * USB)
	Serial	2 * RS232(extendible according to customers requirements)
	PS/2	1 * Keyboard, 1 * Mouse
	LAN	1 * RJ45
	Parallet	1 * LPT
	Audio	1 * Mic-in, 1 * Line-Out
Power	DC-IN	Input AC 100~240V / 50~60hz, Output DC 12V/ 5A
Environment	Temperature	Operating 0~60°, Storage -35°~75°
Size	Dimension	410mm * 265mm * 430mm
	Weight	7.0KG
Optional Peripherals	MSR	ISO 1, 2, 3 Tracks
	Customer Display (CDP)	8-bit VFD customer display or VFD 2 lines * 20 columns
	2nd display	15-inch LCD secondary display Resolution:1024 * 768
Product Reliability	Certifications	CE, FCC, RoHS

