



Single-screen all-in-one Touch POS System

- All in one POS system with all necessary elements put together
- Industrial POS special motherboard
- Eco friendly design with no noise and low consumption
- Space-saving design with built-in power adapter
- Easy tilt angle adjustment, Desktop or wall mount
- 15 inch new original Sharp LED backlight display with Abon 5 wire high temperature process resistive touch panel



JAW-RH668





Colorful design, different colors are customizable for multiple businesses



Wall mounted solution is specially designed for different commercial stores



large angle rotation to meet the needs of different customer segments



Built-in power adapter, space for tidy cabling

Specifications

Item		Specifications
CPU	Intel 1037U	Intel® Celeron® 1037U, Dual Core, 2M Cache, 1.8Ghz
	Intel J1900	Intel® Celeron® J1900, Quad Core, 2M Cache, 2.0Ghz
	Intel i3	Intel® Core® i3-3217U, Dual Core, 3M Cache, 1.8Ghz
OS	Supporting System	Windows xp, Windows 7, Windows 10, POSReady 2009 / POSReady 7
Appearance	Color	White / Black / Red
Main	Memory	DDR3 2GB (up to 8GB)
	Storage	2.5" SATA 500G HDD & 32G / 64G SSD
Primary Display	LCD	15-inch new original Sharp LED backlight LCD
	Resolution	1024 * 768
	Customer Display	8-Bit LED customer display
	Touch Panel	15-inch 5-wire high temperature resistive touch panel from Taiwan Abon
Interfaces	VGA	1 * VGA
	USB	6 * USB(Rear 4 * USB; Side 2 * USB)
	Serial	2 * RS232(extendible according to customers requirements)
	PS/2	1 * Keyboard, 1 * Mouse
	LAN	1 * RJ45
	Parallel	1 * LPT
	Audio	1 * Mic-in, 1 * Line-Out
Power	DC-IN	Input AC 100~240V / 50~60hz, Output DC 12V/ 5A
Environment	Temperature	Operating 0~60°, Storage -35°~75°
Size	Dimension	410mm * 265mm * 430mm
	Weight	5.5KG
Optional Peripherals	MSR	ISO 1, 2, 3 Tracks
	Customer Display (CDP)	8-bit VFD customer display or VFD 2 lines * 20 columns
	2nd display	10-inch TFT secondary display Resolution: 800 * 600
Product Reliability	Certifications	CE, FCC, RoHS



Single-screen all-in-one Touch POS System

- Elegant space saving design.
- Industrial POS special motherboard
- Eco friendly design with no noise and low consumption
- Rich peripheral interfaces to support various POS peripherals
- 15 inch new original Sharp LED backlight display with Abon 5 wire high temperature process resistive touch panel
- 10 inch TFT secondary display specially designed for all kinds of commercial playing



JAW-RH668D





I/O ports placed on the bottom of the panel allow you to easily install and maintain



10 inch TFT LCD with OSD, aims at bringing high quality advertising display



Striping ventilation holes, excellent dissipation capability



Embedded MSR track(1, 2, 3) card reader

Specifications

Item		Specifications
CPU	Intel 1037U	Intel® Celeron® 1037U, Dual Core, 2M Cache, 1.8Ghz
	Intel J1900	Intel® Celeron® J1900, Quad Core, 2M Cache, 2.0Ghz
	Intel i3	Intel® Core® i3-3217U, Dual Core, 3M Cache, 1.8Ghz
OS	Supporting System	Windows xp, Windows 7, Windows 10, POSReady 2009 / POSReady 7
Main	Memory	DDR3 SO-DIMM 2GB (up to 8GB)
	Storage	2.5" SATA 500G HDD & 32G / 64G SSD
Primary Display	LCD	15-inch new original Sharp LED backlight LCD
	Resolution	1024 * 768
	Secondary Display	10-inch TFT secondary display Resolution: 800 * 600
	Touch Panel	15-inch 5-wire high temperature resistive touch panel from Taiwan Abon
Interfaces	VGA	1 * VGA
	USB	6 * USB(Rear 4 * USB; Side 2 * USB)
	Serial	2 * RS232(extendible according to customers requirements)
	PS/2	1 * Keyboard, 1 * Mouse
	LAN	1 * RJ45
	Parallet	1 * LPT
	Audio	1 * Mic-in, 1 * Line-Out
Power	DC-IN	Input AC 100~240V / 50~60hz, Output DC 12V/ 5A
Environment	Temperature	Operating 0~60°, Storage -35°~75°
Size	Dimension	410mm * 265mm * 430mm
	Weight	6.5KG
Optional Peripherals	MSR	ISO 1, 2, 3 Tracks
Product Reliability	Certifications	CE, FCC, RoHS