

21.5 inch Self-Ordering Kiosks

MANTO SERIES

Impressive Visual Experience & Multipurpose

21.5 inch FHD wide viewing angle display, MANTO Series adapts to changing business needs as well as consumers' demands. It serves as product display & advertising, ordering & payment, click & collect, ticketing & e-reservations and whatever business scenarios you wish.

Printer Adaptable

Comparing with traditional self-service kiosk, MANTO Series reduced constraints of printer. Any brands of printer that meet the requirements of dimension will do.

Modular Customizable

Equipped with a wide array of choices of peripherals including 2D scanner, camera and a bracket for EMV payment devices and offering two choices of counter-top or floor-standing. The MANTO Series is able to fulfill with all kinds of self-service tasks.



MANTO SELF-SERVICE KIOSK

The MANTO is the new all-in-one POS terminal. It packs innovativeness and functionality in compact design with stylish look, which is ideal for retail businesses where space is at premium.



MANTO SERIES


21.5 inch Self-Ordering Kiosks

SPECIFICATIONS

Model No.	MAN215W		MAN215A	
SYSTEM				
Processor	Intel Celeron J1900 Quad-Core, Up to 2.42 GHz Intel Celeron J4125 Quad-Core, Up to 2.70 GHz Intel Celeron J6412 Quad-Core, Up to 2.60 GHz Intel Core i3/i5 4th, 5th, 6th, 8th, 10th, 11th, 12th GEN		RK3568 ARM Cortex-A55 Quad-Core, 2.0GHz RK3399 ARM Cortex-A72 Dual-core+Cortex-A53 Quad-core	
Memory	2GB, DDR3L or DDR4, up to 8/16/32GB		4GB DDR4	
Storage	mSata or M.2 SSD, up to 512GB		32GB EMMC	
OS	Windows 10/ 11, POS Ready7		Andriod 11(RK3568), Andriod 10 (RK3399)	
DISPLAY				
Type	21.5 Inch TFT LED Backlight LCD			
Resolution	1920*1080			
Brightness	250cd/m2			
Viewing Angle(CR≥10)	178 Degree(H) 178 Degree(V)			
Touchscreen	Projective Capacitive Touch Screen			
INTERFACE				
USB	4*USB			
Serial	1*COM(RS232)			
LAN	1*Gigabit Ethernet, RJ45			
Power DC-IN	Input AC 100~240V/50~60hz, Output DC12V/7.5A			
SCANNER				
Interface	USB, RS-232 Option			
Image Sensor	1280*800 CMOS			
Illumination	3000K White LED			
Data Capture	1D: Code 11, Code 128, Code 39, GS1-128,(UCC/EAN-128), AIM 128, ISBT 128, Codabar, Code 93, UPC-A/UPC-E, Coupon, EAN-13, EAN-8, ISSN, ISBN, Interleaved 2/5, Industrial 2/5, ITF-14, ITF-6, Standard 2/5, China Post 25, MSI-Plessey, Plessey, GS1 Databar, GS1 Composite, Databar(RSS) 2D: PDF417, QR Code, Data Matrix, Aztec			
Resolution	≥4mil(1D)			
Typical Depth of Field	EAN-13 : 0mm-150mm (13mil) ; QR Code : 30mm-100mm (15mil)			
Scan Angle	Roll: 360° ; Pitch: ±55° ; Skew: ±50°			
Min.Symbol Contrast	25%(Code 128 10mil)			
Field of View	Horizontal 65.6°, Vertical 44.6°			
PHYSICAL & ENVIRONMENTAL				
Printer Space	L160 x W130 x H200mm (Printer is not provided)			
Operating Temperature	Operating 0~60°			
Storage Temperature	Storage -35°~75°			
Cooling	Fanless or with CPU Fan			
Net Weight	Countertop Stand: 21.20KG ; Floor-standing: 23.00KG			
Dimensions(W×H×D)	Countertop Stand: 310x832x310(mm) ; Floor-standing: 500x1596x360(mm)			
Color	Black			
OPTIONS & PERIPHERALS				
WIFI	Mini PCIe for Wireless LAN(Optional)			
Bluetooth	Bluetooth 4.0(Optional)			
Speaker	1*3W			
Payment Terminal Bracket	Adjustable Bracket Optional			

*Specification may change without prior notice.

DIMENSION



FEATURES

